



Power Solutions that empower and protect your business...

Luminous Online UPS with isolation are power packed work horses designed to protect your mission critical applications and equipment from downtime, data loss, corruption and power outages that hamper your productivity and cripple your equipment. LDT series is equipped with state of the art technology and a range of features that includes Isolation Transformer, Input Power Factor Correction and Eco Mode for energy saving to ideally work in a harsh environment. Design innovation coupled with a quality and customer centric attitude is what enabled Luminous to be adjudged as a Super Brand in 2016 once again.

KEY FEATURES

- True double-conversion
- Micro-processor control optimizes reliability
- Input power factor correction
- Wide input voltage (110 V – 280 V)
- ECO mode for energy saving
- Generator compatible
- Wide temperature application (0-50°C)
- Built-in isolation transformer at output
- Comprehensive display allows easy monitoring and access of UPS status

KEY APPLICATIONS

- IT systems and equipment (computers, printers, monitors etc.).
- Process controls, testing & measuring instruments.
- Medical, electronic health-care equipment & Life-support systems in hospitals.
- Safety systems in power stations.
- Audio-Visual equipment.
- Bank branches - ATM's



MODEL	LD1000T	LD2000T	LD3000T
DESCRIPTION	Online UPS with Isolation		
PHASE	Single phase with ground		
CAPACITY	1000 VA / 800 W	2000 VA / 1600 W	3000 VA / 2400 W
INPUT	200/208/220/230/240VAC		
Nominal Voltage	200/208/220/230/240VAC		
Voltage Range	Low Line Transfer	160 VAC / 140 VAC / 120 VAC / 110 VAC \pm 5 % (based on load percentage 100% - 80 % / 80 % - 70 % / 70 - 60 % / 60 % - 0)	
	Low Line Comeback	175 VAC / 155 VAC / 135 VAC / 125 VAC \pm 5 % (based on load percentage 100% - 80 % / 80 % - 70 % / 70 - 60 % / 60 % - 0)	
	High Line Transfer	300 VAC	
	High Line Comeback	290 VAC	
Frequency Range	40Hz ~ 70 Hz		
Power Factor	\leq 0.99 @ Nominal Voltage (100% load)		
OUTPUT	200/208/220/230/240VAC		
Output Voltage	200/208/220/230/240VAC		
Voltage Regulation	\pm 1%		
Frequency Range (Synchronized Range)	47~ 53 Hz or 57 - 63 Hz		
Frequency Range (Batt. Mode)	50 Hz or 60Hz \pm 0.1 Hz		
Current Crest Ratio	3:1		
Harmonic Distortion	\leq 3 % THD (Linear Load), \leq 5 % THD (Non-linear Load)		
Transfer Time	AC to DC	Zero	
	Inverter to Bypass	4 ms (Typical)	
Waveform (Batt. Mode)	Pure Sinewave		
EFFICIENCY	85% max		
To AC Mode	85% max		
To Battery Mode	80% max		
BATTERY	SMF & Tubular (Depending on applications)		
Long-run Model*	Battery Type	SMF & Tubular (Depending on applications)	
	Numbers	3	8
	Charging Current (max.)	2A/4A/8A/12A (Adjustable, up to 12A)	2A/4A/8A/10A (Adjustable, up to 10A)
	Charging Voltage	41.0 VDC \pm 1%	109.4 VDC \pm 1%
INDICATORS	Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicators		
LCD	Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicators		
ALARM	Sounding every 4 seconds		
Battery Mode	Sounding every second		
Low Battery	Sounding twice every second		
Overload	Continuously sounding		
Fault	Continuously sounding		
PHYSICAL	282 x 145 x 332		
Dimension, D x W x H (mm)	282 x 145 x 332	397 x 145 x 332	397 x 145 x 332
Net Weight (kgs)	14	21	23
ENVIRONMENT	0-90 % RH @ 0- 50°C (non-condensing)		
Humidity	Less than 55dBA@1 meter		
Noise Level	Less than 55dBA@1 meter		
MANAGEMENT	Supports Windows 2000/2003/XP/Vista/2008/7/8, Linux, Unix, and MAC		
Smart RS-232/USB	Supports Windows 2000/2003/XP/Vista/2008/7/8, Linux, Unix, and MAC		
Optional SNMP Card	Power management from SNMP manager and web browser		

* Load Derating : 0-40°C@full load / 40-50°C@80% load

** Derate to 80% of capacity in Frequency converter mode and to 80% when the output voltage is adjusted to 200/208VAC

* Product specifications are subject to change without any prior notice

Luminous Power Technologies Pvt. Ltd.
Plot No. 150, 2nd Floor, Sector – 44, Opp. Gold Souk,
Gurgaon -122016, Haryana, India
Phone: +91-1244 776756, Fax: +91-124 2544170

For more information
Call Toll Free: 1800 103 3039 / 1860 500 3939
E-mail: care@luminousindia.com Website: www.luminousindia.com

